

ELIV.DALI.ADD


Auto-addressable WIFI/DALI converter with integrated BUS DALI power supply

Device Wifi to DALI converter with push interface.
Integrated DALI bus power supply for up to 16 devices.
Input Range: 100-240V AC 50/60Hz.
Controllable with Android/iOS/Windows app ELIV.

Input Controls		Output Sync	
Type	Q.ty	Type	Q.ty
Not insulated Push button	1	DALI	1
Wifi	1		

Technical notes

- ✓ Device Wifi to DALI converter with push interface.
- ✓ **Integrated DALI bus power supply for up to 16 devices.**
- ✓ Input Range: 100-240V AC 50/60Hz.
- ✓ **The device is not equipped with earth connection protection against accidental contact with live parts is guaranteed by the enclosure.**
- ✓ Power Connector Cross-section of conductors 14-30 AWG (0.05-2.08 mmq).
- ✓ **Controllable with Android/iOS/Windows app ELIV.**
- ✓ Input Controls: Not insulated Push button x1, Wifi x1.
- ✓ **Output Sync: DALI x1.**
- ✓ Printed Circuit UL.
- ✓ **Protection Class: IP20.**
- ✓ Standard Dimension 40x80x24.45 mm.
- ✓ **Dimension with accessories 40x100x24.45 mm.**
- ✓ Works with the Google Assistant.
- ✓ **Compatible with Amazon Alexa Voice Assistant through the skill ELIV.**
- ✓ All connections must be made with non-live devices and carried out by specialized personnel.
- ✓ **Use only in dry conditions.**



Code	Input voltage	Control inputs	Case	Dimension mm
ELIV.DALI.ADD	100-240V AC	Not insulated push button x1 Wifi x1	YES	40x80 h 24.45

